


Fötter

Everyday



Activity level



| Foot Size | Build Height |
|-----------|--------------|
| 24-25 cm | 184 mm |
| 26-28 cm | 186 mm |
| 29-30 cm | 187 mm |

*Available Sandal Toe Sizes: 24-28 cm

| Impact level | | Weight (kg) |
|--------------|----------|-------------|
| Low | Moderate | |
| 1 | 1 | 44 - 52 |
| 1 | 2 | 53 - 59 |
| 2 | 3 | 60 - 68 |
| 3 | 4 | 69 - 77 |
| 4 | 5 | 78 - 88 |
| 5 | 6 | 89 - 100 |
| 6 | 7 | 101 - 116 |
| 7 | | 117 - 125 |

Foot Module Part Number

F14-00-0 A -

Category 1-7 Size 24-30 Toe configuration
 RU-regular toe, universal
 SR-sandal toe, right
 SL-sandal toe, left

Kinnex

Stay Grounded. Feel Connected.

Freedom Kinnex integrates the world's fastest responding microprocessor ankle/foot technology and carbon fiber to provide low – to moderate impact K3 ambulators the stability they expect – instantly. Unmatched ground compliance, improved comfort, and automated heel height adjustments keep users firmly grounded and connected, wet or dry. Designed for low to moderate K3 level ambulators that require unsurpassed ground compliance for everyday activities. With 30 degrees of microprocessor controlled motion, 20° plantar and 10° dorsi, Kinnex allows the prosthetic user to navigate environmental obstacles such as: ramps, slopes, uneven terrain, and stairs with added confidence and stability. This motion also reduces internal socket pressures and improves the comfort when sitting, squatting or standing.

Features

- Microprocessor controlled resistance to optimize stability on varied terrain, and changes in cadence
- Manual lock: allows for convenient and quick lock out the ankle for driving or certain activities
- IP67 rating for immersion in fresh water for up to 30 min at a depth of 1 m
- Heel height adjustments up to 5 cm
- Feel Connected
- Kinnex GaitLab App for prosthetist use to set up the patient using a smart phone device
- Kinnex Patient App for the user to monitor battery status, make heel adjustments, select shoes and fine tune performance and comfort settings
- Warranty : 36 month

Specs

- User Weight Ratings: 125kg
- Build Height: 184 mm–186 mm (dependent on foot size)
- Average Product Weight: 1.49kg (without footshell)
- Battery Life: 24 hours
- No Power Default Mode: Manual Lock
- Charging Time: 3 hours
- Connector: Male Pyramid
- Warranty Foot Module 36 months,
- Water Resistance: IP67, safe for occasional submersion in water for up to 30 minutes to a depth of 1m